


Oblong Master Links and Multi Master Link without Flattened Section

cromox Multi Master Link for Ropes CAKS. Grade 60 blasted. AISI 318LN (2205 Duplex)


Type	W.L.L. t		Dimensions mm			Weight ca.kg
	45°	60°	d	t	b	
CAKS16/13	1.80	1.25	A 16 B 13	110 110	60 60	1.210
CAKS16/16	2.40	1.70	A 16 B 16	110 110	60 60	1.590
CAKS18/16	3.25	2.25	A 18 B 16	135 110	75 60	1.860
CAKS22/18	5.00	3.50	A 22 B 18	160 135	90 75	3.100
CAKS26/22	8.50	5.95	A 26 B 22	180 160	100 90	5.400
CAKS32/26	10.75	7.50	A 32 B 26	200 180	110 100	8.500
CAKS36/32	13.60	9.50	A 36 B 32	260 200	140 110	14.150



THIS SECTION ON REQUEST

cromox Oblong Master Link CAG. Grade 60 1- and 2-leg. sand blasted. AISI 318LN (2205 Duplex)


Type	W.L.L. t	for Chain		Dimensions mm			Weight kg
		1 - leg	2 - leg	d	t	b	
NEW *CAG 6	0.23			6	60	25	0.043
*CAG 8	0.40	4	-	8	54	30	0.070
KW-CAG10	0.63	5	4	10	80	50	0.150
KW-CAG13	1.55	6/7/8	5/6	13	110	60	0.340
KW-CAG 16	2.45	10	7/8	16	110	60	0.530
*CAG 18	3.55	-	10	18	135	75	0.800
*CAG 22	6.00	13/16	13	22	160	90	1.500
*CAG 26	8.00	18	16	26	180	100	2.300
*CAG 32	12.00	20	18	32	200	110	2.900
*CAG 36	16.00	-	20	36	260	140	6.350



*Not stocked. Available on request.

cromox Multi Master Link CAK. Grade 60 3- and 4-leg. sand blasted. AISI 318LN (2205 Duplex)

Type	W.L.L. t		for Chain	Dimensions mm			Weight kg
	90°	120°		d	t	b	
*CAK 10/ 8	0.80	0.60	4	A10 B 8	80 35	50 19	0.240
*CAK 13/10	1.30	0.90	5	A13 B10	110 44	60 25	0.520
KW-CAK16/13	2.65	1.85	6/7	A16 B13	110 54	60 25	0.970
*CAK 18/16	3.25	2.30	8	A18 B16	135 70	75 34	1.600
*CAK 22/18	5.15	3.65	10	A22 B18	160 85	90 40	2.760
*CAK 26/22	8.15	5.75	13	A26 B22	180 115	100 50	4.450
*CAK 32/26	12.60	9.00	16	A32 B26	200 140	110 65	7.550



*Not stocked. Available on request.